

NJORD® GO IT-NET is a portable 7.4 kW EV charger that gives you fast, reliable Electric Vehicle (EV) charging at home, or when you're on the move. The charger can be used with the CTEK app to give you full Bluetooth and Wi-Fi control over charging current and scheduling, for maximum flexibility.

## SMART, EASY TO USE, FULLY PORTABLE


NJORD® GO IT-NET from CTEK is a durable, lightweight and portable all-in-one EV charger available with a type 2 connector, having a charging capacity up to 7.4 kW. It comes with fixed heavy duty 1.5 m long mains cable and 5 m EV charging cable, so there's no installation necessary – simply plug the unit into your domestic or commercial CEE socket for charging. The charger's user interface clearly indicates charge status. A free to download CTEK app gives you total control over charging and charge scheduling directly from your Android or IOS mobile phone via Bluetooth and Wi-Fi.

The NJORD® GO IT-NET features state of the art natural convection cooling technology, so you can charge at high power even when the ambient temperature is high.

## CTEK APP - TAKE CONTROL OF YOUR EV CHARGING

CTEK app gives you total control over how you charge your EV and when you charge it. Simply connect to your NJORD® GO IT-NET over Bluetooth and Wi-Fi.

- Cost effective type 2, 32 A/1 Phase (7.4 kW) EV charger.
- No installation necessary simply plug the unit into your domestic or commercial CEE socket.
- Small, lightweight portable unit in durable, impact resistant case.
- Intuitive user interface with charging status information.
- CTEK app gives you mobile phone control for Bluetooth and Wi-Fi charging and scheduling.
- Schedule charging for any time of day and for any length of time.
- Lower or increase the power easily to balance the load at times of high domestic power consumption.
- Automatically start, pause or stop charging remotely.
- · View your charging history.





ART. NO	40-352
CHARGING METHOD	Mode 2
CHARGING CATEGORY	AC charging
VEHICLE CONNECTOR	Type 2
MAINS CONNECTOR	CEE 32 A/230 V 3P
NUMBER OF PHASES	1 Phase
CHARGING CURRENT	6-32 A
CHARGING POWER	1.4-7.4 kW
FREQUENCY	50 hz
RATED VOLTAGE (AC)	230 V
AMBIENT OPERATING TEMPERATURE	-30 °C to +50 °C
RELATIVE HUMIDITY	Up to 100 % at 25 °C
COOLING	Natural convection
GROUND FAULT DETECTION	Built-in ground fault detection, 30 mA AC, 6 mA DC
GROUND FAULT RESET	Semi-automatic*
ENERGY METER	Yes, Internal
POSITIONING	Portable, wall mounting
ENCLOSURE DIMENSIONS (H X W X D)	250 x 140 x 80 mm
ENCLOSURE MATERIAL	Plastic, Metal
ENCLOSURE COLOR	Black
CHARGING CABLE LENGTH	5 m
MAINS CABLE LENGTH	1.5 m
NET WEIGHT (UNIT WITH CABLES)	4.3 kg
PACKAGING WEIGHT	4.9 kg
PACKAGING SIZE	435 x 375 x 95 mm
USER INTERFACE	LED symbols
CONNECTIVITY	BLUETOOTH®, Wi-Fi
COMMUNICATION PROTOCOL	OCPP 1.6
COMPATIBILITY MAINS	IT-net
APP SUPPORT	CTEK NJORD app for Android and IOS
INGRESS PROTECTION	IP65
COMPLIANCE	CE, IEC 61851-1, IEC 62196, IEC 62752, EN 60335-1
WARRANTY	2 years

## **GUARANTEED QUALITY WITH CTEK**

Quality is at the heart of everything we do, with safety, simplicity and flexibility characterizing all of our products and solutions. If you have any questions about our products, or would like further information about EV charging, our Customer Support Team is here to help. We are the global leader in battery management solutions, and supply products to more than 70 countries throughout the world. CTEK is also a reliable OEM supplier to many of the world's most prestigious vehicle manufacturers.

For more information visit WWW.CTEKEMOBILITY.COM



<sup>\*</sup>To restore ground faults, the device must be disconnected from the car and from mains voltage.